



Cutting Machine

Automatic J Profile Cutting Machine INVS-CUT 23

Features:

- Managed through the use of electronic counters, and PLC Microcontrolled Keypad with high speed servo motors.
- Material guides are easily adjusted for different application requirements
- J Profile, Flat Plastic Profile Sizes from: 3mm to 40mm width, Multiple Profiles can be processed depending upon width
- Length accuracy: Repeat accuracy $\pm (0.3\% \text{ of length} > 500 \text{ mm})$ $\pm 1 \text{ mm}$ for length $< 500 \text{ mm}$
- Flat cable processing: optional 40 mm width.
- Can process flat and round materials including of PWP Fabric, wires, cables, tubes, sleeves, tapes, labels, and screens and so on in PVC, heat-shrink, rubber, teflon, fibre glass, flat ribbon cables, nylon materials to name a few.
- Wire length range: 1-10000mm
- Bobbin Mounting Stand is optional
- Electrical connection: 220 VAC $\pm 5\%$ 50/60 Hz
- Pneumatic connection required for Cutting Operation
- Dimensions (W x H x D) 465 x 385 x 460 mm
- Weight: 90 kg



Advantages:

- Durable and robust design for longer life
- Multiple material guides for more productivity
- Easy program settings and operations
- Fast and trouble-free transport system
- All electric operations, Low power consumption
- Less wastage, High speed with high accuracy

Details:

Max. Tube (sleeve) Outer Dia.: 20.0 mm (0.8 inch)
Max. Cable Outer Dia: 6.0 mm (0.23 inch)
Maximum Tube Thickness: 1.5mm (0.04 inch depends on material)
Maximum Feed Rate: 1.5 meters per second
Production: 50mm Length 4000 pieces/ hr.
Maximum length: 1mm to 10mtr.
Length Increment: 1 mm (0.0039 inch)
Length Accuracy: $\pm 1 \text{ MM}$ ($L \times 0.3\%$) Depends on the materials
Note: Punching of PWP Fabric Can be Done Automatic Optional

Contact Us

B-40, Muktidham Co.Op. HSG. Society, Road No.22/27, Shreenagar, Wagle Estate, Thane (W) - 400604.
Mobile No.: +91 87790 70985, Mobile No.: +91 87793 03875, Email Id: innvotech_solutions@yahoo.com